

Solicitation/Proposal/Award (Construction)

PROPOSAL

Offerors shall enter in the space below a Total Lump Sum Cost Proposal.

TOTAL LUMP SUM COST PROPOSAL _____

The offeror must furnish the following itemized work division cost break-out, and break-out of total labor and total material, with the proposal or furnish it if and when required by the contracting officer.

1	General Requirements		12	Furnishings	
2	Existing Conditions		13	Special Construction	
3	Concrete		14 - 20	Sections Not Used	
4	Masonry		21	Fire Suppression	
5	Metals		22	Plumbing	
6	Wood and Plastics		23	Heating, Ventilating and Air Conditioning (HVAC)	
7	Thermal and Moisture Protection		26	Electrical	
8	Openings		27	Not Used	
9	Finishes		28	Electronic Safety and Security	
10	Specialties		29- 30	Not Used	
11	Equipment		31	Earthwork	
			32	Exterior Improvements	
			33	Utilities	

Total Labor Breakout: _____

Total Material Breakout: _____

In the event of conflict between the total lump sum cost proposal and either the total of the labor and material break-outs or the total of itemized work division break-out, the total lump sum cost proposal will control.

NOTE: Total Cost for Unit Prices reflected below shall be included in <u>BASE PROPOSAL PRICING</u>.					
Unit Pricing, Reference Specification Sections 03 35 40, and paragraph 5 of Exhibit F, Alterations					
PROPOSAL PRICING FOR UNIT PRICED ITEMS					
INTEROR CONCRETE SLAB ENHANCEMENT, REPAIR AND JOINT FILLER REPLACEMENT (To Be Completed and Returned with Proposal)					
TOTAL ESTIMATED AREA TO BE POLISHED: _____ (SF) Square Feet					
ITEM	AREA FROM ABOVE	MULTIPLIER	TOTAL FROM MULTIPLIER	UNIT RATE INCLUDED IN PROPOSAL PRICING	TOTAL COST INCLUDED IN PROPOSAL PRICING
SAMPLE CALCULATION...NOT PART OF PROPOSAL COST					
Joint Removal and Replacement	32,190	0.14	4,507 LF	\$2.75/LF	\$13,860.00
....DO NOT INCLUDE SAMPLE CALCULATION IN PROPOSAL PRICING					
1. Joint Filler Removal and Replacement		0.14	700 LF	_____/LF	\$_____
2. Spalled joint repair or joint with metal keyway (less than 3/4")		0.08	400 LF	_____/LF	\$_____
3. Spalled joint repair, joint with metal keyway or self-leveling compound removal (greater than 3/4")				\$_____/LF	
4. Crack Repair		0.03	150 LF	_____/LF	\$_____
5a Surface defect repair, including pop-outs, spalls, and gouges 3/4" – 1-1/2" DIA		0.025	125 Units	_____/Unit	\$_____
5b Surface defect repair, including pop-outs, spalls, and gouges 1-1/2" – 3" DIA		0.025	125 Units	_____/Unit	\$_____
6. Surface embed repair, including cleanouts, in-floor electrical outlets and Walker Duct access holes		0.001	5 Units	_____/Unit	\$_____
7. Large surface repair, existing underlayment removal and replacement with 1/4" Polished Overly				\$_____/SF	
8. Grout coat surface enhancement, including micro-pin holes, pitting and other shallow surface deficiencies		0.10	500 SF	_____/SF	\$_____
9. Full Grind, Densify and Polish portions of the project not currently indicated on the drawings				\$_____/SF	