



Security Made Simple

# SCIF-in-a-Box<sup>®</sup>

## IPS Security Container

### TSM621FWX-SC Product Data Sheet

#### TECHNICAL SPECIFICATIONS

<b>Model</b>	<b>TSM621FWX-SC</b>
Max Heat Load:	7400 Watts (at 20°F ΔT)
Rack:	32Ux29"D roll-out rack, 500lb capacity
Weight:	2145lbs
Dimensions:	62.5"H x 27"W x 52"D* add 2.75" to width for vents add 4.6" to depth for handle & cable exit *(Custom Depths Available)
Door Opening:	59.75"H x 24.25"W
Internal Space:	61.75"H x 26.25"W x 38.5"D
Power:	115VAC, 50/60Hz, 2.8A (cooling fans)
Noise Levels:	42dBA at 75°F up to 63dBA at 95°F
Cable Count:	Up to 35 (Cat5) incoming "Black" Up to 75 (Cat5) outgoing "Red"*** **(Optional Enlarged Cable Entry Available)

#### GSA CLASS 5 FEDERAL SPECIFICATIONS:

**PHYSICAL PROTECTION:** Federal Specification AA-C-2786  
 20 man-hours against surreptitious entry  
 30 man-minutes against covert entry  
 10 man-minutes against forced entry

**LOCK SPECIFICATION:** Federal Specification FF-L-2740  
 Approved Locks: Kaba Mas X-10 and S&G 2740



#### FEATURES AT A GLANCE

Largest IPS Container on the market!  
 GSA approved alternative to CAA or facility build-out  
 Highest level class 5 physical protection available  
 32Ux29"D roll-out rack with removable service tracks  
 Quietized temperature controlled cooling fans  
 Two feed-thru style cable entries for Red/Black separation  
 Mounting bracket for optional PDS junction box  
 5-outlet power strip with 15ft cord included  
 Flat bottom design reduces floor loading

#### OPTIONS & ACCESSORIES

Part No.	Description
TSM1010-JB	PDS Junction Box, 10x8x10, Right Side Door Opening
TSM511-ECB	Enlarged Cable Box for High Cable Counts (up to 144 Cat5)
TSM2752-CSTR	Caster Base for 27"Wx52"D models
TSM4X5-SP	Floor Loading Spreader Plate
TSM20DBL4-AEM	Noise Reducing Acoustic "Ear Muffs", for TSM521/621FC models
TSM1926-SLSF	Slide Shelf for 19" Rack, 2U, 26"D
TSM1926-FSF	Fixed Shelf for 19" Rack, 1U x 26"D
TSM5V1USB-D-KVM	KVMGuard HDMI+USB on/off gateway with desktop kill button, for secure SIPR access
TSM5V1RJ45-MS-ENT	EtherGuard Ethernet on/off gateway with desktop kill button, for secure VTC, VOSIP & LAN printer
TSM230V-PTK	European Power Converter with Shuko Plug (for cooling fans only)
TSM5T8SGD-IPS2	SafeGuard Remote Monitor, Alarm & Control System (dial rotation, lock status, door position, temp & power)

Trusted Systems, Inc.  
 2920 Dede Rd, Suite D  
 Finksburg, MD 21048  
 (410) 756-3300 Tel  
 (410) 756-3345 Fax  
 www.trustedsys.com

